

Lenovo ThinkVision T2364t Wide Touch Specifications

Product Specifications Reference (PSREF)

Name Bezel color Type-model Panel Viewable image size Max view area (W x H) Native resolution Touch Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty Available date		T2364t Wide Flat Panel Monitor Black 60E9MAR1US TFT-LCD, In-Plane Switching (IPS), White LED backlight 23.0" (584mm) diagonal 20.05" x 11.28" (509.2mm x 286.4mm) 1920x1080 Supports 10-point touch 16:9 0.2652 x 0.2652 mm 95 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 7ms (typical) 72% 178° (+/- 89°) horizontal, 178° (+/- 89°) vertical Tilt adjustable stand Sides: 0.079" (2.0mm) 12.53" H x 20.56" W x 2.86" D; 318.2mm H x 522.2mm W x 72.7mm D 22 watts typical, 45 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 9.24 lb; 4.32 kg 3 year (includes backlight) June 2015 VESA-compliant Power management Ergonomics Emission standards Environmental VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Gold rating	Features • Widescreen 23.0-inch monitor • Supports 1920x1080 resolution • Includes dual input connection for attachment to two systems concurrently • EPEAT Gold certified • 10-point touch screen • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified
Preset resolutions VGA: 640x350, 640x480, 720x400, 700x570 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 User settings: 20 Presets / user settings		 ThinkVision T2364t	
Viewing adjustments Rotating screen On screen display Control features USB hub Multiple input Monitor connectors Tilt: 10° - 70° degrees; detachable stand None On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness USB 3.0 Hub: 1 port into PC (USB 3.0); 3 ports for accessories (3 USB 3.0) Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, HDMI at each end, digital, 1.8 meter (3) detachable, DisplayPort at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible) Mounting features Security			
Ship group Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter HDMI cable, 1.8 meter DisplayPort cable, 1.8 meter USB signal cable, 1.8 meter black power cord			
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories Kensington MicroSaver Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620 See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	