

ProLite T2234MC-B1X



22" P-Cap 10pt touch screen featuring IPS technology

ProLite T2234MC uses Projective Capacitive Touch Technology, built into an eye catching bezel with Edge to Edge glass. Featuring IPS LCD Screen technology, it offers exceptional colour performance and wide viewing angles , making it a perfect interactive display for Interactive Digital Signage. In addition to the superb image quality , the screen comes with an IP54 Rating, making it dust and water resistant. And, comes with a rugged bezel making it suitable for demanding environments. The screen also features a vast array of inputs including DVI as well as USB for the Touch sensor itself, and a High Definition 1920 x 1080 Resolution. The ProLite T2234MC is the ideal solution for Interactive Digital Signage, Instore Retail, Kiosks, Gaming and Interactive Presentations.

DISPLAY CHARACTERISTICS

| | |
|---------------------|--|
| Diagonal | 21.5" |
| Touchtechnology | projective capacitive, multitouch (10 compatible touch points - supported only under Windows® 7/ 8), activated by finger |
| Panel | IPS LED-backlit |
| Glass hardness | 7H minimum |
| Display area h x w | 268.1 x 476.6 mm; 10.6" x 18.8" |
| Response time | 8 ms |
| Contrast | 1 000 : 1 with touch panel |
| Brightness | 225 cd/m² with touch panel |
| Viewing zone | horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.247 x 0.247 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 31.5 - 82.3 KHz |
| Vertical sync | 56 - 75 Hz |
| Synchronization | Separate Sync |
| Aspect ratio | 16 : 9 |
| Light transmittance | 90% |

INTERFACES & CONNECTORS

| | |
|-------------------------|------------------------------|
| Analog input connector | VGA |
| Digital input connector | DVI-D |
| Inputs | USB (for touch connectivity) |
| | VGA, DVI-D |

SPECIAL FEATURES

| | |
|-------------------|--|
| Controls | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select/ Auto, Power) |
| User controls | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature |
| Anti-theft-device | Kensington-lock™ prepared |
| Safety | CE, TÜV-Bauart, VCCI, IP54 |
| Tilt angle | 90° up; 5° down |
| VESA mounting | 100 x 100 mm |
| Colour | Black |

POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply | DC 12V |
| Power Supply Unit | external |
| Power usage | 40 W typical; max. 3 W in Power management mode |

ACCESSORIES

| | |
|----------------------|---|
| Driver | multi-touch: Windows7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4, Linux, Mac (OSX) |
| Included accessories | AC adapter, power cable, D-Sub signal cable, DVI-D signal cable, USB cable, Touch Panel Driver Disk (CD-ROM), quick start guide, safety guide |
| Optional accessories | remote control OSD key |

DIMENSIONS & WEIGHT

| | |
|----------------------|------------------------|
| Dimensions w x h x d | 517.5 x 351.7 x 219 mm |
| Weight | 7.2 kg |