

Ensure your important presentations look their best with bright, vivid and realistic colours. Utilising Epson's 3LCD projector technology and an equally high White and Colour Light Output, this WXGA projector can produce bright, high-definition images with superb colours even in a variety of ambient light levels.

High-quality content

Showcase your important presentations in the best possible way with the EB-4770W. Thanks to Epson's 3LCD technology, you can be sure that your projected images will feature accurate colours and clear detail. Your images will continue to look their best even in brightly-lit rooms thanks to high brightness and an equally high White and Colour Light Output.

Flexible connectivity

Bring your presentations to life with a range of high-definition content, which can be projected from a variety of devices connected via the HDMI and DisplayPort inputs. Content from these devices can also be displayed alongside content from another source, such as a separate laptop or Epson USB Visualiser, using the side-by-side split screen function.

Easy set-up and maintenance

Setting up the projector is quick and easy thanks to a variety of user-friendly installation features, meaning you can get started quickly. You can place the projector in a number of positions without fear of blurring or distorting the image thanks to its x1.8 wide zoom ratio, keystone correction and arc and point correction. We have also made it easy for you to keep your projections as bright and clear as possible. Both the lamp and filter are easy to replace, meaning maintenance is quick and straightforward

KEY FEATURES

- High brightness 5,000lm White and Colour Light Output
- High definition
 WXGA resolution
- High-quality images 3LCD technology
- Rich, deep blacks 5,000:1 contrast ratio
- Split-screen Connect to different sources





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.59 inch with MLA (D8)
IMAGE	
Colour Light Output	5,000 lumen-3,000 lumen (economy)
White Light Output	5,000 lumen - 3,000 lumen (economy)
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	5,000 : 1
Lamp	280 W, 4,000 h durability, 5,000 h durability (economy mode)
Keystone Correction	Manual vertical: \pm 30 °, Manual horizontal \pm 30 °
High Definition	HD ready
Aspect Ratio	16:10
Colour Processing	10 Bits
, , , , , , , , , , , , , , , , , , ,	
OPTICAL	1.06 0.0001
Projection Ratio	1.26 - 2.30:1
Zoom Dreisetien Sine	Manual, Factor: 1 - 1.8
Projection Size	30 inches - 300 inches
Projection Distance Wide	1.4 m - 8.4 m (300 inch screen)
Projection Distance Tele	2.5 m - 15 m (300 inch screen)
Projection Lens F Number	1.65 - 2.55
Focal Distance	21.28 mm - 37.94 mm
Focus	Manual
Projection Lens Zoom Ratio	1 - 1.8 : 1
Lens	Optical
Lens Shift	Manual - Vertical ± 50 %, horizontal ± 10 %
CONNECTIVITY	
Interfaces	RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n
	(optional), VGA in, VGA out, HDMI in, Display Port, Composite in, BNC in, S-Video in, Stereo
	mini jack audio out, Stereo mini jack audio in (4x), Cinch audio in
ADVANCED FEATURES	
Security	Kensington lock. Security bar, Control panel lock, Password lock
Security Features	Kensington lock, Security bar, Control panel lock, Password lock
Features	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function
Features Video Colour Modes	
Features Video Colour Modes GENERAL	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM
Features Video Colour Modes GENERAL Energy Use	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby)
Features Video Colour Modes GENERAL Energy Use Product dimensions	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height)
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A)
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A)
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity Options	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% MB22 ceiling mount
Features Video Colour Modes GENERAL Energy Use Product dimensions Product weight Noise Level Included Software Loudspeaker Supply Voltage Temperature Humidity Options Sound Pressure	Direct Power on/off, Quick Corner, Six axis color control, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM 388 W, 298 W (economy), 0.39 W (standby) 472 x 354 x 159 mm (Width x Depth x Height) 6.6 kg Normal: 38 dB (A) - Economy: 30 dB (A) EasyMP Monitor, EasyMP Network Projection 10 W AC 100 V - 240 V,50 Hz - 60 Hz Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% MB22 ceiling mount

EB-4770W

WHAT'S IN THE BOX

- CD Manual
- Cable cover
- Computer cable
- Power cable
- Remote control incl. batteries



OPTIONAL ACCESSORIES

- Lamp ELPLP77
 V13H010L77
- Air Filter ELPAF45
- V13H134A45
- Wireless LAN Adapter (b/g/n) ELPAP07 V12H418P13
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14

LOGISTICS INFORMATION

ѕки	V11H748041
EAN code	8715946549767
Dimensions Single Carton	762 x 432 x 324 mm
Carton Weight	12.9 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	16 Units
Pallet Size Block	16 Units



For more information please contact: Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

