

UTCC-VLP1527

Fixed Lens Bullet Camera




KEY FEATURES

- **CCD** 1/3"
- **Resolution** 800 TVL
- **Sensitivity Mono** 0.01 Lux (AGC On, IR Off) / 0 Lux with IR LED On
- **Infra Red IR LEDs** 23
- **IR Range** 10-15m
- **Lens Size** 2.8mm Fixed
- **Voltage** 12V DC
- **Power Consumption** 100mA (275mA IR LED on)
- **Dimensions** Len 182mm, Dia (base) 62mm
- **Weight** 300g

OTHER FEATURES

- Day Night
- Auto White Balance
- Auto Gain Control
- IP65
- 3-Way Mounting
- Internal / External
- Weatherproof
- Pixelplus CMOS Technology
- No Complex OSD
- BNC Video Output
- Standard 12VDC Operation
- IR LED Models for Day/Night Operation
- True Day/Night ICR (ie LED Models)
- 960H Ready



MODEL	VLP1527
Power source	Regulated DC 12V
Power consumption	100mA (275mA IR LED On)
IR LED consumption	175mA 23pc Super Flux IR LED
Scanning system	2:1 Interface
Scanning frequency	15.734KHz(H), 59.95Hz(V)
Effective Pixels	976(H) x 582 (V)
Resolution	800 TVL
E-Shutter	PAL 1/25 - 15000s ; NTSC: 1/30 - 15000s
ACG/BLC	On
WB	AWB
Sync System	Internal
Min. Illumination	0 Lux IR LED On
Video output	1.0 Vp-p (75 ohm, composite)
S/N Ratio	more than 47dB (AGC OFF)
Video output	BNC Connector
Lens mount	Fixed mount
Lens	Fixed Lens models 2.8mm
Operating temperature	-10°C to +50°C / 14°F to 122°F
Operating humidity	Up to 90% (non-condensing)

