ThinkCentre Tiny-in-One (TIO) 24

Product Specifications Reference (PSREF)

				_					
Model	10LLPAR6++ / 10LLPAT6++			Μ	ounting features		Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPMI [®] (100mm mount) <i>Tilt:</i> 35° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°		
Form factor	Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into the back of TIO 24, clean cabling and effortless setup			A	djustable stand				
Compatible Tiny:	M900 Tiny, M700 Tiny, M600 Tiny, M93/p Tiny*, M83 Tiny, M73 Tiny*, or M53 Tiny, Chromebox * Non-TIO models can't be turned on by pressing power button of TIO 24				Power supply90 watts AC/DC adapter, 88% PSU, universalPower consumption16.7 watts typical, 35 watts maximum, <0.5 watts standby / suspend				
				Li	Limited warranty ³ 3-years , Customer Carry-In or Mail-In via Rapid Replacement Service				
Panel Viewable image size Max view area (W x H) Bezel Width Optimum resolution Aspect ratio	areă (W x H) 21.06" x 12.32" / 535.0mm x 313.0mm h Top / Side: 2mm, Bottom: 16.3mm esolution 1920x1080 o 16:9				ESA-compliant ² rgonomics mission standards nvironmental /indows certifications	VESA DDC2B/CI, VESA DPMS-compliant ISO 9241-307 FCC Class B TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY STAR® 7.0 EPEAT™ Gold rating, ULE Gold, TUV, VOC Windows 7, Windows 8/8.1, and Windows 10 certified			
Pixel pitch (mm) Dot/Pixel per Inch	0.2745mm 92.6 dpi				hip group	TIO 24 (Monitor), detachable stand, AC/DC power adapter, power cord, user's guide and driver CD, guick start and safety poster			
Brightness Contrast ratio	250 nits or cd/m ² (typical) 1000:1 (typical)				ccessories	For compatible accessories, please go to http://www.lenovoguickpick.com			
Pixel response time	7ms 72% Anti-glare R178° (+/- 89°) horizontal, 178° (+/- 89°) vertical			-					
Color gamut Anti-reflective						ThinkCentre Tiny-in-One 24 Compatible list			
Viewing angle at 10:1 C					Model	M900 Tiny, M700 Tiny, M600 Tiny,	M93/p Tiny,	Chromebox	
Preset resolutions	640x350 @ 70Hz 640x480 @ 60Hz, 66Hz, 72Hz, 75Hz 720x400 @ 70Hz 800x600 @ 60Hz, 72Hz, 75Hz 1024x768 @ 60Hz, 70Hz, 75Hz					M83 Tiny, M53 Tiny	M73 Tiny		
					Turn on TIO and Tiny together via Alt + P on USB KB	All models	All models	Not support	
	1152x864 @ 75Hz 1280x800 @ 60Hz 1280x1024 @ 60Hz, 72Hz, 75Hz 1366x768 @ 60Hz 1440x900 @ 60Hz, 75Hz 1600x1200 @ 60Hz, 70Hz, 75Hz 1680x1050 @ 60Hz 1920x1080 @ 60Hz Presets: 25; user settings: 25				Turn on TIO and Tiny together via TIO Power Button	All models	TIO models	All models	
Presets / user settings									
On screen display Control features	On screen display with digital user controls (8 languages) Mode-switching (TIO mode / standalone monitor mode, switches video / audio / USB input sources) / Back button, Left shift button, Right shift / Brightness button, Selection button / Menu button, Power button								
Tiny-in-One Power On	Pressing Alt + P on keyboard or pressing Power button positioned on TIO can turn on both TIO and Tiny (only some Tiny support, see compatible list)								
Front ports	Two USB 3.0 or two USB 2.0 (when M73 or M53 installed or USB 2.0 connected via USB upstream port), one headphone / microphone combo jack (3.5mm) * The USB ports are only available when a Tiny is istalled or a PC is								
Side ports Rear ports 3-in-1 Cable	connected via USB upstream port Side ports offered by installed Tiny (optional) One DisplayPort 1.2 port, one USB upstream port, one power connector Undetachable 3-in-1 cable (Power connecter, USB 3.0 [supports USB 3.0/ USB 2.0], DisplayPort 1.2), only for connecting to Tiny installed (optional)								
Internal Speaker	1.5 watt x1								
Security	Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO 24 together, more security features offered by Tiny installed (optional)								
Mechanical	Dimensions	TIO 24 without stand	TIO 24 with stand]					
	W x D x H (inch)	21.24 x 2.7 x 13.64	21.24 x 9.90 x 15.16 - 19.46						
	W x D x H (mm)	539.6 x 68.2 x 346.45	539.6 x 251.4 x 385.08 - 495.08						
	Weight (approximately)	ht 12.25 lb /5.57 kg (with stand)							
See footnotes for more de	tailed information							© Lenov	