



HP EliteDisplay E243d 23.8-inch Docking Monitor

Touch down to an instant workspace

Make the most of your desk with streamlined USB-C™¹, network, and accessory connectivity, plus a pop-up HD webcam, with the HP EliteDisplay E243d 23.8-inch Docking Monitor, our most advanced 23.8" docking display.



Maximum efficiency in a modern, minimalist footprint

- Create a command center from a display and built-in docking station that's ready to drive your workspace as soon as you plug in. Power your notebook and send and receive video over driverless USB-C™.¹ Connect your wired network through the RJ-45.

Control your window to the world

- Reveal more of your work and support virtually seamless tiling with a 60.45 cm (23.8") diagonal IPS FHD screen and 3-sided micro-edge bezel. Daisy chain a second display² from one PC connection with a DisplayPort™ output.

Expand your view

- Experience a virtually seamless dual-display setup with 3-sided micro-edge bezels when you daisy chain a second display from a single USB-C™ connection on your PC.⁵

Featuring

- Save time by leaving your USB devices connected to one of the 4 USB 3.0 ports, and access your network through the RJ-45. Maintain legacy compatibility with VGA, HDMI, and DisplayPort™ out ports.
- Work comfortably with adjustable tilt, height, and swivel settings. Use pivot rotation to conveniently customize portrait or landscape views.
- Do even more with an easy clean desk solution. Attach your HP EliteDesk Mini Desktop PC directly behind the display and power it through the USB-C™ connection.
- Design the screen for how you work with HP Display Assistant software, which enables screen partitioning and helps deter theft by dimming a display that's disconnected without approval.
- Rest assured that your IT investment is supported by a three-year standard limited warranty.

HP EliteDisplay E243d 23.8-inch Docking Monitor Specifications Table



Display type	IPS with LED backlight
Brightness	250 nits ¹
Contrast ratio	1000:1 ¹
Response Ratio	7 ms gray to gray ¹
Product colour	Asteroid bezel and Jack black stand
Aspect ratio	16:09 ¹
Native resolution	FHD (1920 x 1080 @ 60 Hz)
Resolutions supported	1280 x 1024; 1280 x 720; 1280 x 768; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400; 800 x 600
Display features	Anti-glare; Anti-static; BrightView panel; In plane switching; Language selection; LED backlights; Low haze; On-screen controls; Pivot rotation; Plug and Play; User programmable
User controls	Brightness; Color control; Contrast; Exit; Image control; Information; Input source; Language; Management; Menu; Power; USB host selection
Input signal	1 HDMI 1.4; 1 VGA; 1 USB Type-C™ (Alternative mode DisplayPort™ 1.2, power delivery up to 65 W); 1 USB Type-B ^{4,5} (with HDCP support for USB-C™ and HDMI)
Display size (diagonal)	23.8"
Display size (diagonal, metric)	60.45 cm (23.8")
Ports and Connectors	1 audio-in; 1 headphone-out; 1 RJ-45; 1 USB 3.1 (fast charging, power delivery up to 7.5 W); 3 USB 3.1 (power delivery up to 4.5 W); 1 DisplayPort™ 1.2-out ^{1,5}
Camera	720p integrated HD with dual array microphone and LED
Environmental	Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing;
Power	100 - 240 VAC 50/60 Hz
Power consumption	155 W (maximum), 38 W (typical), 0.5 W (standby)
Dimensions	53.88 x 4.535 x 32.19 cm (Without stand.)
Weight	6.2 kg (With stand.)
Physical security features	Security lock-ready ³
Certification and compliance	Australian-New Zealand MEPS; BSMI; BSMI AS/NZS 3548 Class B; CB; CCC; CE; cTUVus; EAC; FCC; ICES; ISO 9241-307; KC; KCC; Microsoft WHQL Certification (Windows 10, Windows 8.1 and Windows 7); NOM; PSB; SmartWay Transport Partnership (NA); TUV-S; UL; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; China Energy Label (CEL) Grade 3
Sustainable impact specifications	Arsenic-free display glass; Low halogen; Mercury-free display backlights ²
What's in the box	AC power cord; Documentation; HDMI cable; USB Type-C™ cable; USB Type-A to B cable; DC-DC cable; DC jack dongle; External power supplier; QSP; Product notice
Warranty	5 years next business day onsite support
Pixels per inch (ppi)	93 ppi
Panel bit depth	8 bit (6 bit + FRC)
Vertical viewing angle	178°
Horizontal viewing angle	178°
Bezel	3-sided micro-edge
Swivel	±45°
Tilt	-5 to +23°
Pivot	±90
Height adjustment range	150 mm
VESA mounting	100 mm x 100 mm (bracket included)
Screen treatment	Anti-glare
Flicker-free	No
Low blue light modes	Yes
Energy efficiency class	F
Display scan frequency (horizontal)	30-80 KHz
Display scan frequency (vertical)	50-60 Hz
Pixel pitch	0.274 mm

HP EliteDisplay E243d 23.8-inch Docking Monitor

Accessories and services (not included)

HP B300 PC Mounting Bracket



Customize an altogether better solution with the HP B300 PC Mounting Bracket, which lets you attach your HP Workstation, HP Desktop Mini, HP Chromebox or select HP Thin Client directly behind select 2017 and 2018 HP EliteDisplays and HP Z Displays.¹
Product number: 2DW53AA

HP DisplayPort Cable Kit



Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor.
Product number: VN567AA

HP 5 year Next business day Onsite
Standard Monitor Hardware Support



Receive 5 years of next business day onsite HW Support from an HP-qualified technician for your computing device, if the issue cannot be solved remotely.
Product number: U7935E

HP EliteDisplay E243d 23.8-inch Docking Monitor

Messaging Footnotes

¹ Video over USB-C™ requires a PC with USB-C™ DisplayPort™ Alt mode or Thunderbolt™. Power delivery over USB-C™ up to 65 Watts. Refer to Power Output in product QuickSpecs for exact specifications, PC must be compatible with the display's power output.

² Additional displays sold separately.

³ Internet access required and sold separately.

⁵ Additional display sold separately. Source PC must have a USB-C™ or USB-A connector. PC connection to the display through USB-C™ is only supported up to 65 Watts power delivery. USB-A connection requires source PC to support DisplayLink. Not compatible over DisplayPort™, VGA or HDMI connections.

⁶ HP EliteDesk Mini Desktop PC, sold separately. must have a USB-C™ port. Requires HP B300 PC Mounting Bracket for Monitors, sold separately.

⁷ Power up to 65 Watts through USB-C™.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.

² External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

³ Lock is sold separately.

⁴ 1 USB Type-C™ with HDCP support.

⁵ Only one host PC should be connected to either USB Type-C™ port or DC OUT port for Power pass through. Connecting two Host PCs to the HP EliteDisplay E243d 23.8-inch Docking Monitor may result in system shutdown, loss of power, and the need to power-cycle the monitor's AC supply.

Sign up for updates hp.com/go/getupdated

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. Thunderbolt is a trademark of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

4AA7-4214, March 2021

