## ThinkPad X1 Extreme Gen 3 Platform Specifications

Processor	10th Generation Intel® Core™ i5 / i7 / i9 Processor											Dimensions	WxDxH (non-touch): 14.24" x 9.67" x 0.72"; 361.8mm x 245.7mm x 18.4mm
	Processo Number	Cores	# of Thread	ls Fre	quency	Max Tu Freque	ncy Cache	Memoi	ry Types	Proce Grap		Weight	WxDxH (multi-touch): 14.24" x 9.67" x 0.74"; 361.8mm x 245.7mm x 18.7mm Non-touch model: starting at 3.75 lb / 1.7 kg; Multi-touch model: starting at 4.0 lb / 1.81 kg
	i5-10400l i7-10750l i7-10850l	H 6	12	2.0	6 GHz 6 GHz 7 GHz	4.6 GH 5.0 GH 5.1 GH	Hz 12MB	DDR4	4-2933	Intel I Grap		Case color Case material	Black paint or black weave  Display cover: CFRP/GFRP hybrid; Bottom: Aluminum alloy
Graphics	Intel UHD Graphics in processor only or Intel UHD Graphics in processor and NVIDIA® GeForce® GTX 1650 Ti Max-Q, 4GB GDDR6 memory; supports up to 4 independent displays via native display and 3 external monitors; supports external monitors via HDMI (up to 4K@60Hz) or Thunderbolt™ (up to 5K@60Hz for hybrid model / 4K@60Hz for integrated model)											Smart card reade Media reader Ports	rNone SD Card reader, supports UHS-II SD card (mutually exclusive with WWAN card) Two USB 3.2 Gen 1 (one Always On), two USB 3.2 Type-C Gen 2 / Thunderbolt 3 (with the function of Power Delivery and DisplayPort 1.4 for discrete graphics / DisplayPort 1.2 for integrated graphics) HDMI 2.0, nano-SIM card slot (WWAN models), headphone / microphone combo jack, SD card reader, security keyhole, slim tip AC adapter *Depending on many factors, actual data transfer speed may be lower than theoretical speed
Chipset Memory	Mobile Intel WM490 Chipset 64GB max / 2933MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets * Installed memory is actually 3200MHz but run at 2933MHz due to Intel limitation										ockets		<ul> <li>Lenovo HDMI to VGA Monitor Adapter</li> <li>Lenovo USB-C to VGA Adapter</li> <li>Lenovo USB-C to DisplayPort Adapter</li> </ul>
Display	Size Res	solution	Т	ype	Surface	Touch	Brightness		Contrast	Color	Viewing	Bundled Accy	Optional: Lenovo USB-C to Ethernet Adapter
	15.6" FHI	D (1920x		,	inti-glare	-	300 nits	Ratio 16:9	700:1	Gamut 72% NTSC	Angle 170°	Audio support	<ul> <li>Description</li> <li>HD720p camera with ThinkShutter camera privacy, fixed focus</li> <li>IR camera and HD720p camera with ThinkShutter camera privacy, fixed focus</li> <li>HD Audio, Realtek® ALC3286 codec /</li> </ul>
	15.6" FHI			VVA A	nti-glare	-	500 nits	16:9	800:1	72% NTSC	170°		Dolby® Atmos™ sound system with 3-magnet speakers, 2W x 2 / optional dual array microphone, headphone / microphone combo jack
	-	D (3840x by Vision			nti-glare		600 nits	16:9	1400:1	100% Adobe	178°	- Keyboard - UltraNav™	6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, LED backlight TrackPoint® pointing device and buttonless glass surface multi-touch touchpad
	15.6" UH Dol	D (3840x by Vision	2160) HDR	LED	AR, AS	Multi- touch	SDR 400nit, HDR 540nit (peak)	16:9	100000:1	100% 1 DCI- P3	170°	Security Security chip	Power-on password, hard disk password, supervisor password, security keyhole • Firmware TPM 2.0 integrated in chipset
Multi-touch (opt)  Pen (optional)  Storage	Capacitive-type multi-touch, supports 10-finger gesture, anti-reflection (AR), anti-smudge (AS) coating Lenovo Pen Pro  Up to two M.2 SSD											Fingerprint reader	Discrete TPM 2.0 TCG Certified stem Mgt (opt) Intel vPro Technology gerprint reader Touch style match on chip fingerprint reader on the keyboard bezel lor calibration Optional: X-Rite Pantone factory color calibration (UHD model only) C None
RAID (optional) Optical	M.2 2280 SSD / PCIe NVMe 3.0 x 4 RAID 0/1 support											Battery	Integrated Li-Polymer 80Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 135W AC adapter
Ethernet		Gigabit Ethernet connection via optional Lenovo USB-C to Ethernet Adapter										Max battery life	
WLAN + BT	Intel Wi-Fi 6 AX201, Wi-Fi 2x2 802.11ax + Bluetooth™ 5.1											* Battery life varies significantly with hardware configurations, settings, usage, & other factors	
WWAN (optional)	N (optional) Integrated Mobile Broadband 4G LTE-A, Fibocom L860-GL, MIMO 2x2, M.2 card										AC adapter	135W or 170W slim tip AC adapter (170W for ig-10885H model only)  Optional: Windows® 10 Home 64 or Windows 10 Pro 64	
SIM card	* For non-WWAN model, it means the model is NOT WWAN upgradable None												·
											Mil-Spec test	MIL-STD-810G military testing	
												Environment	EPEAT™ Gold; ENERGY STAR® 8.0; TCO Certified; RoHS-compliant