

Easy to use, versatile printer with cloud connectivity



DellTM Mono Multifunction Printer - B2375dfw

Connect and collaborate wirelessly within your network and the cloud with the B2375dfw printer. This versatile device features a range of document management solutions to digitize, store, sort and share your files with ease.

Access personalized printer settings on the 4.3-inch color touch screen control panel — the easiest to use in its class¹. Scan and copy two sided documents easily with the Duplex Automatic Document Feeder (DADF) and reduce paper consumption with two-sided printing.

Get outstanding value and reliable performance with the Dell Mono Multifunction Printer - B2375dfw.

1. Comparison based on manufacturers' published specifications and includes monochrome A4 laser MFPs <\$499 and printing speed of 31-44 ppm (Letter), available Aug 2013 based on market models as reported by IDC Hardcopy Peripheral Tracker Q2, 2013.

Dell Mono Multifunction Printer | B2375dfw



Print, scan and share with cloud connectivity

- Scan and share directly to multiple destinations, including PCs, USB drives, email, network folders, FTP, Web Services for Device (WSD) and cloud services including Microsoft® SharePoint® Online and Google Drive™.
- Scan and convert hard copies to Google Docs format from Google Drive.
- Streamline workflows by storing and accessing frequently-used forms and templates directly from the printer (up to 3 GB built-in accessible storage).
- Manage documents easily with included Nuance[™] PaperPort 14, which converts scanned documents into high-quality, searchable PDF files for easy storage, sorting and sharing.




Wireless versatility and security

- Set up and connect easily to your wireless network with Dell Printer Easy Wifi Installer in as fast as four clicks.
- Print directly from a variety of mobile devices with:
- Dell Mobile Print app (for Android™ mobile devices)1
- AirPrint (for iOS mobile devices)²
- Google Cloud Print™
- Gain the assurance of document and printer security with multi-level security features such as Secure Print, Secure PDF and user walk-up LDAP authentication.



Intuitive functionality for ease of use

- Personalize user settings on 4.3-inch color touch screen, the easiest to use control panel in its class³, and preview scanned documents directly on the touch screen before sharing and printing.
- Print at fast speeds of up to 40/38 pages per minute⁴ (letter/A4).
- Handle large printing needs reliably with a high monthly duty cycle⁵ of up to 100,000
- pages. • Scan and copy two-sided documents effortlessly with the 50-page Duplex Automatic Document Feeder (DADF).
- Reduce paper consumption with two-sided printing.



Optional 520-sheet input tray



Increase the input capacity of the B2375dfw to 820 sheets with the optional 520-sheet input tray

Product Specifications				
Physical specifications	Dimensions (W x D x H)	Printer: 18.2" x 16.5" x 18.8" (462 mm x 420 mm x 477 mm)		
Thysical specifications		Shipping: 23.6" x 21.9" x 23.7" (599 mm x 556 mm x 601 mm)		
	Weight	Printer: 36.37 lb (16.5 kg) with consumables; Shipping: 40.12 lb (18.2 kg)		
	Operating environment	Temperature: 10°C to 32°C; Relative humidity: 20% to 80% RH, non-condensing; Altitude: < 8,200 ft		
	Storage	Temperature: 10°C to 32°C; Relative humidity: 20% to 80% RH, non-condensing; Altitude: < 8,200 ft		
	Acoustics (Pressure/Power)	Printing – 57 dB ⁶ , Standby – 30 dB ⁶		
Power specifications	Voltage			
	120 VAC model	110 to 127 VAC \pm 10 %, 50 \pm 3 Hz / 60 \pm 3 Hz nominal		
	Power consumption	Ready mode: 60 W; Power saver mode: 4 W (Sleep)		
	Environmental compliance	ErP Lot 4 and 6, RoHS-compliant ⁷ , ENERGY STAR [®] qualified ⁸ , Blue Angel (Germany) 2013, WEEE, CEL (China), CECP, EPEAT [®] registered in US and Canada ⁹		
Supported languages	English, French, German, Italian, Spanish, Dutch, Danish, Norwegian, Swedish and Finnish			
Connectivity	Standard interfaces	High speed USB 2.0 client port, Gigabit Ethernet port, Wireless 802.11 b/g/n, USB Embedded Host Port for USB Direct Print and Scan		
Operating Systems	Windows	Microsoft® Windows 8, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008 R2 SP1, Windows Server 2008 SP1 6, Windows 7, Windows 7 SP1, Windows XP SP3, Windows Server 2003 SP1. Windows Server 2003 SP2, Windows Vista SP1, Windows Vista SP2		
	Macintosh	Macintosh OS X 10.5 to 10.8		
	Others	Red Hat Linux [®] Enterprise Desktop 4, 5, 6 (32/64 bit), Fedora 5 to 15 (32/64 bit), OpenSuSE 10.2 to 11.4 (32/64 bit), Mandriva 2007 to 2010 (32/64 bit), Ubuntu 6.06 to 11.04 (32/64 bit), SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debiam 4.0 to 6.0 (32/64 bit); Sun Solaries 9 to 11 (x86, SPARC), HP-UX 11.0 to 11i v3 (PA-RISC, Itanium), IBM AIX 5.1 to 5.3; Novell [®] Netware 5.x and 6.x with iPrint; SAP R/3 Release 4.5B onwards; Citrix [®] XenApp 4.5 to 6.5		
Product certifications	Safety certifications	IEC60950-1:2005 2nd Edition (International); EN60950-1:2006/A11:2009/A1:2010/A12:2011; EC60825-1 2nd (Laser); SEMKO (Nordic); CE Mark (EU); UL/cUL listed (UL60950-1 2nd Edition, US/Canada); FDA/DHHS (21 CFR, Chapter 1, Subchapter J)		
	Other certifications	CE mark (EU countries) EMC/Safety Standard Class B, EN55022:2006; EN55022:2010; EN61000-3-2:2006; + A1:2009 + A2:2009; EN 61000-3-3:2008; EN 55024:1998+A1:2001/A2:2003; FCC CFR Titl 47, Part 15 Class B (USA); ICES-003, Issue 4 (Canada);		
Mobile printing support	Dell Mobile Print ¹⁰ (Android™ OS), AirPrint ¹¹ (iOS). Google Cloud Print			
Printer management	Dell Printer Configuration Web Tool, Dell Toner Management System, Dell Open Printer Driver (OPD), Dell OpenManage TM Printer Manager v2 (OMPM)			
Security features	Print Job Management	Secure Print with 4 Digit Pin, Virtual Mail Box		
	Network Authentication	NTLM (Scan To SMB only), Kerberos/Digital cert, self signed, CA signed, SNMP V3		
	Access Control Management	Admin lock network, Printer Settings, Reports, Control panel lock, Feature lock: copy, scan, fax, USB host printing, Acess to Google Drive, Scan to Microsoft® SharePoint™ Online, My Calendar, My Files, My Forms		
	I/O Access control	Direct I/O Port (USB, USB Front) Disable/Enable, Protocol Base (Network), Fax/I/O control (Enable/Disable)		
	Wireless Security	WPA – TKIP, WPA2 - Personal, WPA2 – Enterprise – IEEE 802.1x (Wireless), WEP – 64/128 bits		
	MFP Authentication	Copy/Scan/Print feature lock using OPP common Password Address book with LDAP Kerberos User Authentication		
	Fax Security	Secure Fax received		
	Lock type and location	Kensington lock for printer, Kensington lock for optional secondary input tray		
	Consumable lock type and encryption	Toner cartridge CRUM electronics locked		
Contents in box	Dell Mono Multifunction Printer – B2375dfw, Ship-With Black Cartridge (3,000-page yield ¹), Power cord, Setup Diagram, Quick Reference Guide, Important Information, Telephone Line Cord, Drivers and Documentation CD, PaperPort 14 CD			



1. The printer and the mobile device must be connected to the same network

2. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later. 3. Comparison based on manufacturers' published specifications and includes monochrome A4 laser MFPs <\$499 and printing speed of 31-44 ppm (Letter), available Aug 2013 based on market models as reported by IDC Hardcopy Peripheral Tracker Q2, 2013.

Hardcopy Peripheral Tracker Q2, 2013. 4. Measured in accordance with ISO IEC 27434 methodology. Actual print speeds will vary with use. 5. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers. 6. For details on energy efficiency of ENERGY STAR^a qualified products, refer to: www.energystar.gov 7. Meets the requirements of the EU ROHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS). 8. EPEAT registration varies by country. See www.epeat.net for registration status by country.

Toner yield based on testing in accordance with ISO/IEC 19752. Yields vary with usage and environmental conditions.
 For a copy of Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or visit dell.com/warranty. For warranty information on other countries, see website: dell com/servicecontracts and then select the country.
 Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.
 Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.
 Renote Diagnosis is the determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty (dell.com/warranty) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.
 Availability and terms of Dell Services vary by region. For more information, visit dell.com/servicedescriptions.
 Tested in accordance with ISO 9779 and reported in accordance with ISO 9296. Acoustics - Declared noise emission values of computer and business equipment
 Meets the requirements of the EU ROHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (ROHS).
 Evo dealise on peercy efficiency of ENPERCY STAPP uselified for the two we pergentations.

Meets the requirements or the ED KORS DIRELWE 2010 FLOW END OF the Restriction of the USE of Certain Trazeroous Substances (w).
 For details on energy efficiency of EDKRGY STAR® qualified products, refer to: www.energystar.gov
 EPEAT registration varies by country. See www.epeat.net for registration status by country.
 Configuration of the printer and the mobile device must be on the same authorized wireless network.
 AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.

Warranty and service options		
Standard service	1 Year Limited Hardware Warranty ² and 1 Year Advanced Exchange Service ³ after Remote Diagnosis ⁴	
Service upgrade options	 2 - 5 Years Advanced Exchange Service³ after Remote Diagnosis⁴ 1 - 5 Years On-site Service after Remote Diagnosis⁴ 1 - 5 Years Advanced Exchange ProSupport^{™ 5} after Remote Diagonosis⁴ 1 - 5 Years On-site ProSupport^{™ 5} after Remote Diagnosis⁴ 1 - 5 Years On-site with On-site Resolution ProSupport^{™ 5} 	

Printer specifications	Print speed (Mono / Color)	Up to 40 ppm ¹ (letter, simplex) and 38 ppm ¹ (A4, simplex) and Up to 17 ppm ¹ (letter/A4, duplex)
rinter specifications	First page out time from Ready state	Less than or equals to 15.5 seconds (simplex)
	Print resolution	600 x 600 dpi, (up to 1200 dpi image quality)
	Operation panel	4.3" Color Touch Screen, 480 x 272 pixel; Viewing Area: 53.8 mm x 95 mm; Backlight: White backlight ;
		Buttons: 9 Buttons; Status LED: 1 LED ("Ready" and "Error"); Energy Saver Button: Yellow Light
	Print language	Driver Language: PCL 5e, 6 version; Postscript 3; XPS; IPP Raster format (URF, PWG); Data stream (FW): PCL 5e Emulation, PCL 6 Emulation, PostScript 3 Emulation, XPS, IPP Raster format (URF, PWG)
	Fonts	93 Scalable Fonts and 1 bitmap in PCL136 scalable PS fonts
	Processor speed	1 GHz
	Memory	1 GB ²
	Storage type	MicroSD 4 GB ² (3 GB ² usable space)
	Maximum duty cycle	Up to 100,000 pages per month ³
	Recommended monthly print volume	750 - 4,000 pages per month
Scan specifications	Scan sensor assembly	Flatbed, CIS with LED illumination
	Scan resolution	Flatbed scan Optical: 600 x 600 dpi, ADF scan Optical: 300 dpi x 300 dpi, Software Enhanced: 4800 x 4800 dpi (max)
	Scan to media (file format)	TIFF (Single/Multi), JPEG, PDF (V1.6), XPS
	Pull scan file types (Client)	Client support: Application dependent; Device support: PDF (v1.6), TIFF, Multi-TIFF, JPEG
	Walk-up scan to: list supported network type	Scan to: Email, PC, Network PC, Network Folder, FTP Fax Server, WSD, Google Drive™, Microsoft®
	Walk-up scap to: address hs -1-	SharePoint Online
	Walk-up scan to: address book	Common Address book: 200
	Directory Access	Active Directory LDAP Search
	Scan size (max)	Flatbed: 8.5" x 11.69" (216 mm x 297 mm); DADF: 8.5" x 14" (216 mm x 356 mm)
Copy specifications	Copy speed	Up to 40/38 cpm (Letter/A4, simplex, 1 to N)
	First copy out time	From Ready Mode: 10 seconds (Platen) and 15 seconds (DADF)
	Copy resolution	600 x 600 dpi (Flatbed)
	Maximum copies	199
	Zoom	25% - 400% (Plate/DADF)
	Copy features	Eco Copy, ID Card Copying, Auto Fit Copying, Poster Copying, Clone Copying, 2-up or 4-up copying (N- up), Book Copy, Margin Shift, Collate Copy
Fax specifications	Modem speed/Fax transmission speed	Up to 33.6 Kbps
	Speed dial	Up to 200 entries
	Fax feature	Transmit: Broadcast, Delay/Schedule, Forward, PC Fax; Receive: Secure, Remote
Automatic Document Feeder	ADF type	Duplex Automatic Document Feeder (DADF)
ADF)	Input capacity	50 sheets (75 gsm), 35 sheets (105 gsm), 40 sheet (90 gsm)
	Media type (weight)	50 gsm – 125 gsm
	Media size	Letter, Legal, Oficio, Folio, A4, B5, Executive, A5: Custom paper size (Min): 5.7" x 5.7" (145 mm x 145 mm); Custom paper size (Max): 8.5" x 14" (216 mm x 356 mm)
Standard media types, sizes	Standard tray	
	Media types and weights supported	16 to 43 lb (60 to 163 gsm) Plain paper, Cardstock, Recycled, Bonded, Thin paper, Thick paper, Archive paper
	Media sizes	Letter, A4, Legal, Oficio, Folio, A5, A6, Executive, JIS B5, ISO B5
	Multipurpose tray	Custom size (Min): 3.86" x 5.85" (98 mm x 148 mm); Custom size (Max): 8.5" x 14" (216 mm x 356 mm)
	Media types weights supported	16 to 58 lb (60 to 220 gsm) Plain paper, Preprinted, Colored paper, Cardstock, Recycled, Labels, Envelope,
	Media sizes	Transparency, Bonded, Cotton, Thin paper, Thick paper, Thicker paper, Archive paper Letter, Legal, A4, Oficio, Folio, Executive, A5, A6, Post Card 4x6, Envelope (No 9, No 10, DL, C5, C6, Monarch),
	Optional tray	JIS B5, ISO B5, Custom size (Min): 3" x 5" (76.2 mm x 127 mm); Custom size (Max): 8.5" x 14" (216 mm x 356 mm)
	Media types and weights supported	16 to 43 lb (60 to 163 gsm) Plain paper, Cardstock, Recycled, Bonded, Thin paper, Thick paper, Archive paper
	Media types and weights supported Media sizes	Letter, A4, Legal, Oficio, Folio, A5, A6, Executive, JIS B5, ISO B5
		Custom size (Min): 3.86" x 5.85" (98 mm x 148 mm); Custom size (Max): 8.5" x 14" (216 mm x 356 mm)
	Duplexer	16 to 70 lb (60 to 120 gcm) Disin paper Presided Presided This area to
	Supported media type (weight)	16 to 32 lb (60 to 120 gsm) Plain paper, Recycled, Bonded, Thin paper
	Media sizes	Letter, A4, Legal, Oficio, Folio
Dapar Handling	Printable area	3 mm margin around the paper size
Paper Handling	Standard input sources	250-sheet standard tray, 50-sheet multipurpose tray
	Additional input capacity	520-sheet option tray
	Maximum input capacity	820 sheets (via addition of one 520-sheet optional tray)
	Duplexer	Standard two-sided printing
	Output capacity	250 sheets

Measured in accordance with ISO IEC 27434 methodology. Actual print speeds will vary with use.
 1 MB means 1 million bytes, 1 GB means 1,000 megabytes or 1,000,000,000 bytes; total accessible capacity varies depending on operating environment.
 Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.

©2013 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation. Android and Google Cloud Print are registered trademarks of Google Inc. [Pad, IPhone, IPAd, IPAd touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc., Specifications are subject to change without notice. Dell cannot be responsible for errors and omissions in typography or photography.

A13002263 - B2375dfw - Oct 2013