


The 22SM3B with the smart platform based on webOS is effective for simple and easy content management. With built-in Wi-Fi, it provides network convenience to simplify installation and to manage content efficiently. It is suitable for small spaces to deliver promotional messages and event information at in-store promotion rack, meeting rooms, and a conference hall, etc.

NEXT

Key Features



8 Retriv Provide Receive BEACON Coupoi a Coupoi data Signa

Device 1 Device 2



NETWORK

Business Solutions

Intuitive Information Delivery



22SM3B

• Brightness : 250 cd/m²

- Bezel : Top/Left/Right/Bottom 16.3 mm (Even Bezel)
- Depth : 53.8 mm
- Special : BEACON support, Wi-Fi Built in (Mirroring, Soft AP)
- Interface : HDMI / USB / RGB / RJ45 / IR
- Built-in Speaker : 1W x 1W


22SM3B

Specifications

PANEL	Screen Size	21.5
	Panel Technology	IPS
	Aspect Ratio	16:9
	Native Resolution	1,920 × 1,080 (FHD)
	Brightness	250 cd/m ²
	Contrast Ratio	1,000:1 (Typ.)
	Dynamic CR	4,000,000:1
	Viewing Angle (H x V)	178 x 178
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1%(Typ.))
	Guaranteed Operating Hour	16 Hours
	Orientation	Landscape
CONNECTIVITY	Input	HDMI, RGB, Audio, USB 3.0
	Output	-
	External Control	RS232C In, RJ45 In, IR Receiver In (Built-in), Pixel Sensor In
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	16.3 mm (T/R/L/B)
	Monitor Dimension (W x H x D)	510.3 x 302.1 x 53.8 mm
	Weight (Head)	3.6kg
	Carton Dimensions (W x H x D)	565.0 x 357.0 x 103.0 mm
	Packed Weight	4.7kg
	VESA [™] Standard Mount Interface	100 x 100 mm
SPECIAL FEATURES		ISM Method, Internal Memory 8GB (System 4GB + Free 4GB), Wi-Fi (802.11n Combo Built-in), USB Cloning, Local Contents Scheduling, Sync Mode, PM Mode, Local Time Auto Setting, Wake on LAN, Pivot Mode, Content Rotation (0,90,270), Fail Over, BEACON On/Off, Embedded Template
ENVIRONMENTAL	Operating Temperature Range	0 °C to 40 °C
CONDITIONS	Operating Humidity Range	10 % to 80 %
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
		35W
	Power Iyp. Consumption Smart Energy Saving	On 25.13W / Off 29.76W
AUDIO POWER	i Sindi encey Saving	2W(1W x 2) for Internal Speaker
STANDARD	Safety	UL/cUL/CB/TUV
(CERTIFICATION)	EMC	FCC Class "A" / CE
SOFTWARE	Content Management Software	SuperSign W
	Control and Monitoring Software	SuperSign C
ACCESSORY	Basic	Remote Controller (2 Batteries Included), Power Cord, QSG, RGB Cable, Phone to RS232C Gender
	Optional	Pixel Sensor (KT-SPO), Wall Bracket (RW120)
	optional	

Dimension (unit : mm)

22" 510.3 x 302.1 x 53.8 / 3.6kg



Connectivity

RS-232C IN AUDIO IN **3** PIXEL SENSOR 4 LAN HOMI

G RGB IN 6 HDMI IN USB 3.0



Download LG Commercial Display Mobile App



oyoutube.com/c/LGECommercialDisplay https://www.facebook.com/LGInformationDisplay/

🕞 www.lg.com/b2b

in https://www.linkedin.com/company-beta/16235211/

LG may make changes to specifications and product descriptions without notice. Copyright © 2018 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.

The names of products and brands mentioned here may be the trademarks of their respective owners.



