

Lenovo ThinkVision P27 Specifications

Product Specifications Reference (PSREF)

Name Case color Type-model Panel Viewable image size Max view area (W x H) Optimum resolution Max pixel rate Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD, including stand) Power supply Weight Limited warranty⁴ Available date	P27 Wide Flat Panel Monitor Black 60E3GAR1US TFT-LCD, IPS (In-Plane Switching), White LED backlight 27" (684.7mm) diagonal 23.49" x 13.21" (596.7mm x 335.7mm) 3840x2160 600MHz 16:9 0.16 x 0.16mm 163 dpi 300 nits or cd/m² (typical) 1300:1 (typical) 6ms 99% 178° horizontal, 178° vertical Tilt, swivel, pivot, and height adjustable stand Sides: 0.088" (2.23mm) 18.59" H x 24.19" W x 11.81" D; 472.3mm H x 614.5mm W x 299.9mm D 40 watts typical, 70 watts maximum (with USB), <0.5 watts sleep/off; <0.5 watts switch off 15.12 lb; 6.86kg (including stand) 3 year March 2016	Features • 27-inch IPS LED backlit monitor with speaker • Supports 3840x2160 resolution • 5-Ports USB hub, support USB 3.0 • 3watts x 2 stereo speakers • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified						
VESA-compliant² Power management Ergonomics Emission standards Environmental	VESA DDC2B/CI ENERGY STAR® 7.0 ISO 9241-307 FCC Class B TCO Displays 7.0, RoHS, EPEAT™ Gold rating, ULE Gold	 ThinkVision P27 Monitor						
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x720, 1280x768, 1280x800, 1360x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080, 1920x1200 UHD: 3840x2160							
Preset / user settings	Standard presets: 20; user settings: 20							
Viewing adjustments Rotating screen On screen display Control features USB hub Multimedia Camera Multiple input Monitor connectors Signal cables Mounting features Security	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 3.15" (80mm); <i>swivel:</i> +/-45° Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (touch buttons on front) for menu, mute, volume up/down, and brightness USB Hub: one USB 3.0 upstream port, four USB 3.0 downstream ports Integrated stereo speakers (3 watts x 2) None Support HDMI, DisplayPort (1) HDMI (1.4), digital, HDCP-compliant (2) DisplayPort (1.2), digital, HDCP-compliant (1) detachable, DisplayPort at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)							
Ship group	Monitor, detachable stand, Quick start and safety poster, 1.8 meter DisplayPort cable, 1.8 meter USB 3.0 cable, 1.8 meter black power cord, mini DP to DP adapter, power adapter (90W)							
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> </table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303
Kensington MicroSaver Cable Lock	73P2582							
Kensington Twin Head Cable Lock	45K1620							
Lenovo Security Cable Lock	57Y4303							

See footnotes for important warranty information

© Lenovo
(P27) March 2016