

## W416

## HD ready, compact and powerful

- Bright WXGA projector 4500 ANSI Lumens
- Installation flexibility Vertical lens shift and 1.6x zoom
- Ultimate Control Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- Easy connectivity HDMI, MHL, VGA, 10W speaker





















#### W416

Make your presentations count regardless of the ambient light level using the bright HD ready W416. Designed for businesses and professional installation environments this compact and powerful projector can be installed or taken on the move.

Easy to connect to with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even present wirelessly using the HDCast Pro (sold separately) or use the USB Power to connect and power HDMI dongles such as the Google Chromecast.

For more complex installations, this projector is equipped with a large 1.6x zoom range, vertical lens shift and networking features for remote monitoring and control.d control.

#### Large zoom range

A large zoom range enables multiple placement possibilities at a variety of distances from the projection screen. An advantage to this is that expensive interchangeable lens projectors can be substituted with a more cost effective solution whilst still retaining a diverse choice of positioning options.

#### MHL

Turn your projector into a smart display by connecting your smartphone or tablet with a single cable using MHL; now you can view presentations and documents, stream videos and share photos on the big screen. You can even use MHL to connect and power the HDCast Pro (sold separately).

#### Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

#### **Eco AV mute**

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

#### **Auto power off**

There may be instances when the projector is left running when not in use. To help save energy, the "Auto Power Off" feature automatically turns off the projector after a set period of time if it is not being used

#### **High contrast**

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.





#### Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.

#### Long lamp life

Reduce the number of lamp changes with lamp life of up to 6500 hours

#### Colour guarantee

Enjoy dazzling colours for years to come; guaranteed by Optoma for five years' consistent performance.





#### **Vertical lens shift**

Simplify installation with vertical lens shift, which provides a wider range of projector placement possibilities. This makes it easier to position the projector in your room and enables a wider range of screen size options.

#### **USB** power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast.

#### Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

#### **Energy saving**

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

#### **Quick resume**

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

#### **Wireless**

Stream Full 1080p 3D content to your projector wirelessly; eliminating the hassle and extra cost of installing long cables, the WHD200 (sold separately) allows you to connect a Blu-ray™ player, set-top box, gaming console or AV receiver instantly.

#### Remote mouse and laser

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control and built in laser pointer

#### **Networking and control**

Featuring a wide range of options you can remotely control and monitor the projector.

#### RS232

Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.

#### **AMX Compatibility**

Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.

#### LAN Control

Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.

- · Schedule the projectors to power on/off.
- Control and alter the projector settings using the simple web browser.
- Emergency text broadcast capabilities for urgent or important announcements.
- Automatically receive email updates for lamp maintenance.

#### **Amazing colours**

For vibrant, natural looking images, Optoma projectors incorporate BrilliantColor™ multi-colour processing technology.





without

WILLI

### **W416 Specification**

Native Resolution	t 3.5mm
Contrast   20,000:1	t 3 5mm
Amp Life   Eco+/Dynamic/Eco/Bright   7000/6000/5000/3000 (hrs)	t 3 5mm
Throw Ratio   1.47 - 2.35:1	it 3.5mm
Throw Ratio	ıt 3 5mm
Zoom Type	ıt 3 5mm
Lens Shift	ıt 3 5mm
Various   Vari	ıt 3 5mm
RS232, RJ45, USB-A Power, USB mouse/service	AL O. OITHIII.
Keystone Correction         ± 40° Vertical           Weight (kg)         2.99           Dimensions (W x D x H) (mm)         286 x 224 x 114           Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         96.2% ~ 112.4%           Projection Screen Size         0.65m - 7.7m (25.66" ~ 303.2") Diagonal 16:10           Projection Distance         1.3 - 9.6m           Projection Lens         F/2.5~3.26; f=20.91~32.62mm           Uniformity         75%           Computer Compatibility         UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3C games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080i50 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60           Over-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15 - 91kHz           Vertical Scan Rate         24 - 120Hz	,
Weight (kg)         2.99           Dimensions (W x D x H) (mm)         286 x 224 x 114           Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         96.2% ~ 112.4%           Projection Screen Size         0.65m - 7.7m (25.66" ~ 303.2") Diagonal 16:10           Projection Distance         1.3 - 9.6m           Projection Lens         F/2.5~3.26; f=20.91~32.62mm           Uniformity         75%           Computer Compatibility         UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3S games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080j50 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60         Over-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15 - 91kHz           Vertical Scan Rate         24 - 120Hz	
Dimensions (W x D x H) (mm)         286 x 224 x 114           Aspect Ratio         16:10 Native, 16:9/4:3 Compatible           Offset         96.2% ~ 112.4%           Projection Screen Size         0.65m - 7.7m (25.66" ~ 303.2") Diagonal 16:10           Projection Distance         1.3 - 9.6m           Projection Lens         F/2.5~3.26; f=20.91~32.62mm           Uniformity         75%           Computer Compatibility         UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           Video Compatibility         PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p           3D Support         Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.           3D Compatibility         Side-by-Side:1080i50 / 60, 720p50 / 60           Frame-pack: 1080p24, 720p50 / 60         Over-Under: 1080p24, 720p50 / 60           Horizontal Scan Rate         15 - 91kHz           Vertical Scan Rate         24 - 120Hz	
Aspect Ratio  16:10 Native, 16:9/4:3 Compatible  Offset  96.2% ~ 112.4%  Projection Screen Size  0.65m - 7.7m (25.66" ~ 303.2") Diagonal 16:10  Projection Distance  1.3 - 9.6m  Projection Lens  F/2.5~3.26; f=20.91~32.62mm  Uniformity  75%  Computer Compatibility  Video Compatibility  PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  3D Support  Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility  Side-by-Side:1080i50 / 60, 720p50 / 60  Frame-pack: 1080p24, 720p50 / 60  Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate  15 - 91kHz  Vertical Scan Rate  24 - 120Hz	
Offset 96.2% ~ 112.4%  Projection Screen Size 0.65m - 7.7m (25.66" ~ 303.2") Diagonal 16:10  Projection Distance 1.3 - 9.6m  Projection Lens F/2.5-3.26; f=20.91~32.62mm  Uniformity 75%  Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate 15 - 91kHz  Vertical Scan Rate 24 - 120Hz	
Projection Screen Size  0.65m – 7.7m (25.66" ~ 303.2") Diagonal 16:10  Projection Distance  1.3 - 9.6m  Projection Lens  F/2.5~3.26; f=20.91~32.62mm  Uniformity  75%  Computer Compatibility  Video Compatibility  PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  Tell 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility  Side-by-Side:1080i50 / 60, 720p50 / 60  Frame-pack: 1080p24, 720p50 / 60  Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate  15 - 91kHz  Vertical Scan Rate  24 - 120Hz	
Projection Distance Projection Lens F/2.5~3.26; f=20.91~32.62mm Uniformity 75% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15 - 91kHz Vertical Scan Rate 24 - 120Hz	
Projection Lens F/2.5~3.26; f=20.91~32.62mm  Uniformity 75%  Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate 15 - 91kHz Vertical Scan Rate 24 - 120Hz	
Uniformity 75%  Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate 15 - 91kHz  Vertical Scan Rate 24 - 120Hz	
Computer Compatibility  UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  Video Compatibility  PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  3D Support  Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility  Side-by-Side:1080i50 / 60, 720p50 / 60  Frame-pack: 1080p24, 720p50 / 60  Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate  15 - 91kHz  Vertical Scan Rate  24 - 120Hz	
Video Compatibility  PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p  Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility  Side-by-Side:1080i50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate  15 - 91kHz  Vertical Scan Rate  24 - 120Hz	
SD Support  Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical application with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility  Side-by-Side:1080i50 / 60, 720p50 / 60  Frame-pack: 1080p24, 720p50 / 60  Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate  15 - 91kHz  Vertical Scan Rate  24 - 120Hz	
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  3D Compatibility Side-by-Side: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15 - 91kHz Vertical Scan Rate 24 - 120Hz	
games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.  Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15 - 91kHz Vertical Scan Rate 24 - 120Hz	s include use
3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15 - 91kHz Vertical Scan Rate 24 - 120Hz	o™ and 3D
Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60  Horizontal Scan Rate 15 - 91kHz  Vertical Scan Rate 24 - 120Hz	
Horizontal Scan Rate         15 - 91kHz           Vertical Scan Rate         24 - 120Hz	
Horizontal Scan Rate         15 - 91kHz           Vertical Scan Rate         24 - 120Hz	
Vertical Scan Rate 24 - 120Hz	
Displayable Colours 1.07 Billion	
Noise Level (Eco mode) 32dB	
Power Supply 100-240V, 50-60Hz	
Power Consumption 309W Bright mode / 249W Eco mode (<0.5W Standby)	
Lamp Type 260W	
Security Security har, Kensington lock, password protection	
On Screen Display  19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian	,Greek,
Standard Accessories AC power cord, remote control, 2x AAA batteries, quick start card, CD user manual	
Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount	
Optional Wireless Yes	
RoHS Compliant	
Colour Guarantee <sup>3</sup> 5 Years	



# Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

<sup>1</sup>Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

 $^2$ Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

04/07/2016 16:01