



G2260VWQ6

21.5
(54.6) LCD MONITOR

Featuring AMD FreeSync™ technology to eliminate tearing, stuttering and input lag, the 21.5-inch AOC G2260VWQ6 also boasts a 1ms response time and the innovative Anti-Blue Light technology, which reduces eye fatigue for a more comfortable viewing.

144_{Hz}

144hz

FREE
SYNC

FreeSync



Speakers




Vesa Wallmount



1ms Response Time

A pixel response time of 1ms GTG means speed without the smear for an enhanced experience.

Fast-moving action and dramatic transitions will be rendered smoothly without the effects of ghosting.



FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.



DisplayPort Connection

The most recent display interface standard from VESA, DisplayPort can also transfer audio, USB and other forms of data. DisplayPort version 1.2-1.2a support up to 165 Hz@1440p, 75 Hz@2160p, version 1.3 supports up to 240Hz@1440p, 120 Hz@2160p and the version 1.4 supports HDR10 specifications.



Display Port

The most recent display interface standard from VESA, DisplayPort can also transfer audio, USB and other forms of data. DisplayPort version 1.2-1.2a support up to 165 Hz@1440p, 75 Hz@2160p, version 1.3 supports up to 240Hz@1440p, 120 Hz@2160p and the version 1.4 supports HDR10 specifications.

Screen Details

| | |
|--------------------------|---|
| Color | Black |
| Resolution | 1920x1080 PX |
| Refresh rate | 75Hz |
| Response time | 1 |
| Panel | TN |
| Backlight | WLED |
| flickerfree | ✓ |
| Aspect ratio | 16:9 |
| Brightness (typical) | 250 |
| Contrast (dynamic) | 20M:1 |
| Contrast (static) | 1000:1 |
| Pixel Pitch (H) (V) | 248 |
| Diagonal (inch) | 21.5 |
| Active Screen Area (HxW) | 477.5x268.5 mm |
| Viewing angle (CR10) | 170/160 ° |
| Display Colours | 16.7 Million |
| OSD languages | EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP |

Connections

| | |
|--------------|--|
| Signal Input | HDMI 1.4 x 1, VGA, DisplayPort 1.2 x 1 |
|--------------|--|

What's in the box

| |
|--|
| VGA cable (1.8m m), HDMI cable (1.8m m), Displayport Cable (1.8m m), Power Cable C7 (1.8 m), |
|--|

Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Ergonomics

| | |
|----------------|----------|
| Swivel | 0 ° |
| Tilt | -5/+20 ° |
| Vesa Wallmount | 100x100 |

Power details

| | |
|-------------------|--|
| Powersupply | Internal |
| Powersource | 100 - 240V 50/60Hz |
| Power Consumption | On 20 watt, Off 0.3 watt Standby 0.5 watt, |

Dimensions

| | |
|--------------------------------|----------------------|
| Product Dimensions (incl base) | 511.8x376.9x184.4 mm |
| CartonDimensions | 693x127x435 mm |
| Net Weight (excl package) | 3.03 |
| Gross Weight (incl package) | 4.15 |

Warranty

| | |
|----------------|---------------|
| WarrantyPeriod | 3 Years |
| EAN | 4038986125314 |
| MTBF | 50.000 hours |

Regulations

| |
|--------|
| TCO 6, |
|--------|

