## **EPSON A3+/A2+ PHOTO PRINTERS QUICK REFERENCE GUIDE – SPECIFICATIONS**

	Epson Stylus <b>Photo 1400</b>	Epson Stylus Photo R2000	Epson Stylus <b>Photo R2880</b>	Epson Stylus Photo R3000	Epson Stylus <b>Pro 3880</b>
IMAGE QUALITY Ink type Ink brand Number of colours	Dye Epson Claria Photographic 6 colour: C/M/Y/Lm/Lc/K	Pigment Epson UltraChrome Hi-Gloss2 7+1 colour: Pk/Mk/C/M/Y/Or/R/Go	Pigment (4th generation) Epson UltraChrome K3 with Vivid Magenta 8+1 colour: C/VM/Y/Pk/Mk/Llk/Lk/ Lvm/Lc	Pigment (4th generation) Epson UltraChrome K3 with Vivid Magenta 8+1 colour: C/VM/Y/Pk/Mk/Llk/Lk/ Lvm/Lc	Pigment (4th generation) Epson UltraChrome K3 with Vivid Magenta 8+1 colour: C/VM/Y/Pk/Mk/Llk/Lk/ Lvm/Lc
HARDWARE AND DRIVER Resolution (dpi) Head technology Min. droplet size <sup>1</sup> ICC profile as standard Advanced Black & White mode	5760x1440 optimised resolution Epson Micro Piezo printhead with VSDT 1.5pl Yes No	5760x1440 optimised resolution Epson Micro Piezo printhead with VSDT 1.5pl Yes No	5760x1440 optimised resolution Epson Micro Piezo printhead with VSDT 3pl Yes Yes	5760x1440 optimised resolution Epson Micro Piezo printhead with VSDT 2pl Yes Yes	2880x1440 Epson Micro Piezo printhead with VSDT 3.5pl Yes Yes
PRODUCTIVITY Ink change from MBk to PBk Cartridge size Individual cartridges	- 11ml Yes	Built-in 17ml Yes	Manual 11.4ml Yes	Auto ink switch 25.9ml Yes	Auto ink switch 80ml Yes
PRINT SPEED Max. A4 plain paper (black)² Max. A4 plain paper (colour)²	15ppm 15ppm	13ppm 13ppm	9ppm 9ppm	9ppm 9ppm	3ppm 3ppm
CONNECTIVITY Ethernet / Wireless³ USB 2.0 PictBridge™ support	- Yes Yes	Built-in Ethernet and Wireless 802.11 b/g/n Yes Yes	– Yes, Dual Port Yes	Built-in Ethernet and Wireless 802.11 b/g/n Yes Yes	Built-in Ethernet Yes No
MEDIA SUPPORT Supported media width Borderless print Automatic sheet feeder Roll paper Fine Art Paper support Thick Media support Duplex CD/DVD print	9x13cm (3.5x5in) up to 32.9x48.3cm (13x19in) (A3+) Yes Yes No No No Manual Yes	9x13cm (3.5x5in) up to 32.9x48.3cm (13x19in) (A3+) Yes Yes Yes Yes Yes, up to 1.3mm Manual Yes	9x13cm (3.5x5in) up to 32.9x48.3cm (13x19in) (A3+) Yes Yes Yes Yes up to 1.3mm Manual Yes	9x13cm (3.5x5in) up to 32.9x48.3cm (13x19in) (A3+) Yes Yes Yes Yes up to 1.3mm Manual Yes	9x13cm (3.5x5in) up to 42x59.4cm (16.5x23.4in) Yes Yes No Yes Yes, up to 1.5mm Manual No
BUNDLED SOFTWARE	Epson Creativity Suite incl. Epson Easy Photo Print, FileManager, Web to Page, RawPrint, Print CD	Epson Creativity Suite incl. Epson Easy Photo Print, FileManager, Web to Page, Camera RAW Plug-in for Epson Creativity Suite, Epson Print CD, EpsonNet Setup	Epson Creativity Suite incl. Epson Easy Photo Print, Web to Page, Epson FileManager, Camera RAW Plug-in for Epson Creativity Suite, Epson Print CD, Adobe® Elements (PC) / (Mac®)	Epson Easy Photo Print Epson Print CD EpsonNet Setup	-
ENVIRONMENTAL FEATURES Power consumption max./min. Noise level	16W / 1.5W 47dB(A)	21W / 3.7W 39dB(A)	20W / 4W 40dB(A)	21W / 3.7W 38dB(A)	25W / 5W 39dB(A)

 $\oplus$ 

 $\oplus$ 

 $\oplus$ 

For more information please contact:

Telephone: 0871 222 6702 (UK)\* 01 436 7742 (Republic of Ireland) E-mail: Chat: Fax: enquiries@epson.co.uk etalk.epson-europe.com 0871 222 6740

Measured using this print sample at draft mode.

Web: www.epson.co.uk www.epson.ie

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.



 $\oplus$ 

 $\oplus$ 

## **EPSON A3+/A2+ PHOTO PRINTERS QUICK REFERENCE GUIDE**

						EPSON ULTRACHRONE KBik VIVID MAGENTA		
Size		A3+/13"	A3+/13"	A3+/13"	A3+/13"	A2/17"		
Number of inks		••••						
Choose the right printe for the application	er	Epson Stylus <b>Photo 1400</b>	Epson Stylus <b>Photo R2000</b>	Epson Stylus <b>Photo R2880</b>	Epson Stylus <b>Photo R3000</b>	Epson Stylus <b>Pro 3880</b>		
Printing colour photos		√	1	1	1	√		
Printing colour photos with high	est gloss finish	Due to dye based Claria Photographic Ink	Due to pigment based UltraChrome Hi-Gloss2 with Gloss Optimiser			-		
Printing black & white photos		-	Due to UltraChrome K3 with Vivid Magenta Ink with 3 levels of black					
Printing Fine Art originals & repro	oductions	-	Due to pigment ink which supports a variety of media					
Printing documents and present	tations	1	√	√	1	√		
Printing panoramics & banners		-	Supports roll paper to print up to 3	29mm width and 3,276mm length	Supports roll paper to print 329mm width and 3,276mm length	-		
Printing on thick media e.g. poster boards		-	Up to 1.3mm due to straight paper path Up to 1.5mm due to straight paper path					
CAD/GIS		-	Due to Micro Piezo printhead and pigment ink which gives sharp thin lines					
Proofing (with additional RIP sof	tware)	-	- Supported by a number of RIP vendors					
Photobooks/Scrapbooking/Arts & Crafts		√	1	1	1	$\checkmark$		
CD/DVD printing		J	↓ ↓	√	1	-		
Connectivity	Benefit							
Wi-Fi <sup>1</sup>	Place the printer where you want	-	1	-	1	-		
Ethernet	Implement easily into your network	-	1	-	1	√		
Hi-speed USB 2.0	Easy plug & play installation	1	1	1	1	1		
PictBridge™	Print directly from your digital camera	1	1	1	1	-		
Extra features	Benefit							
Permanent printhead	No need to replace, cost reduction	1	1	1	1	1		
Durable pigment ink set	Print long lasting pictures on a variety of media	-	1	1	V	1		
ENERGY STAR®	Certified low power consumption	1	1	-	1	1		

<sup>1</sup> Some or all Wi-Fi products may not be available in certain countries. Wireless n standard is available in EU countries only.



 $\oplus$ 

\_\_\_\_

 $\oplus$ 

## **EPSON PERFECTION SCANNERS QUICK REFERENCE GUIDE**

					anta Tanàna amin'ny faritr'o dia mandritry dia mandritry dia mandritry dia mandritry dia mandritry dia mandritry dia	0			
Choose the right scanner for the application		Epson Perfection V33	Epson Perfection V330 Photo	Epson Perfection V500 Photo	Epson Perfection V600 Photo	Epson Perfection V700 Photo	Epson Perfection V750 Pro		
Scanning documents & photos		1	1	√	1	1	1		
Scanning films		-	With Optical density 3.2	With Optical density 3.4		With Optical density 4.0			
35mm film & slides		-	6 frames / 4 slides	12 fram	es / 4 slides	24 frames / 12 slides			
Medium format film & panoramics		-	-	One 6x12cm strip	One 6x22cm strip		Two 6x20cm strips		
Larger film formats		-	-	-	-	Up to 20.3x25.4cm			
Scanning using Fluid Mount Accessory (FMA) (oil scanning)		-	-	-	-	Option B12B818272	Available upon application in some regions Option B12B818272		
Restoring damaged and dusty films		By software	By software	Due to	Due to Digital ICE <sup>™</sup> hardware-based infrared scanning technology				
Restoring damaged and dusty photos		By software	By software	By software By software Due to Digital ICE <sup>™</sup> hardware-based dual light source scanning					
Scanning 3D objects e.g. jewellery or wa		Due to CCD <sup>1</sup> sensor technology which gives a higher depth of field							
Scanning text documents for digitising c	-		Due to bundled ABBYY FineReader® OCR software with output option to Word, Excel or searchable PDF						
Scanning larger than A4 originals and ou	utput as single image	-	Due to bundled software ArcSoft Scan-n-Stitch <sup>™</sup>				1		
Scanning multi-page documents without feeding manually each page		_	-	Feeder (ADF) as Option B12B813392	-	-	-		
Extra features	Benefit								
ReadyScan LED technology	Low power consumption and near instant startup	1	1	1	1	-	-		
Multiple output formats	Save scanned images directly as standard image types			Save as Bitmap, Jpeg	g, Tiff, Multi-Tiff and PDF				
Text Enhancement	Sharper texts when scanning a document	1	1	1	1	1	1		
Photoshop Elements bundled	Edit and enhance scanned images with fully-featured software	-	-	1	1	1	1		
Prof. scanning software bundled	Enhance scan results with professional solutions from SilverFast®	-	-	-	-	Silverfast® SE	Silverfast® Ai		
Colour management software bundled	Create ICC profiles for your scanner with MonacoEZColor	-	-	-	-	-	1		
Connectivity	Easy plug & play installation on Windows® & Mac®	Hi-speed USB 2.0	Hi-speed USB 2.0	Hi-speed USB 2.0	Hi-speed USB 2.0	Hi-speed USB 2.0 & IEEE1394	Hi-speed USB 2.0 & IEEE1394		
ENERGY STAR®	Certified low power consumption	1	1	1	1	1	1		

<sup>1</sup> Charge-Coupled Device

 $\oplus$ 

 $\oplus$ 

 $\oplus$ 

## **EPSON PERFECTION SCANNERS QUICK REFERENCE GUIDE – SPECIFICATIONS**

	Epson Perfection <b>V33</b>	Epson Perfection V330 Photo	Epson Perfection V500 Photo	Epson Perfection V600 Photo	Epson Perfection V700 Photo	Epson Perfection V750 Pro
Sensor	CCD <sup>1</sup>	CCD <sup>1</sup>	CCD <sup>1</sup>	CCD <sup>1</sup>	CCD <sup>1</sup>	CCD <sup>1</sup>
Optical resolution	4800x9600dpi	4800x9600dpi	6400x9600dpi	6400x9600dpi	6400x9600dpi	6400x9600dpi
Optical density (DMAX)	-	3.2	3.4	3.4	4.0	4.0
Light source	White LED	White LED	White LED	White LED	CCFL <sup>2</sup>	CCFL <sup>2</sup>
Pixel depth (In/Out)	16/16bit	16/16bit	16/16bit	16/16bit	16/16bit	16/16bit
Max output resolution	12800dpi	12800dpi	12800dpi	12800dpi	12800dpi	12800dpi
Interface	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0 and IEEE 1394	USB 2.0 and IEEE 1394
Max effective area	216x297mm	216x297mm	216x297mm	216x297mm	216x297mm	216x297mm
Transparency Unit	-	Built-in	Built-in	Built-in	Built-in	Built-in
Supported film types	-	35mm strip x 6 frames 35mm slide x 4 frames	35mm strip x 12 frames 35mm slide x 4 frames Medium format 6x12cm	35mm slide x 4 frames 35mm strip x 12 frames Medium format 6x22cm	35mm slide x 12 frames 35mm strip x 24 frames Medium format 6x20cm 5x4in two frames Up to 8x10in on scanbed	35mm slide x 12 frames 35mm strip x 24 frames Medium format 6x20cm 5x4in two frames Up to 8x10in on scanbed
Film holder storage	-	In scanner lid	-	-	-	-
Automatic Document Feeder	-	-	Optional: 30 sheet capacity, 60-105gsm, 4ppm	-	-	-
Buttons	Four buttons: Start, copy, scan to e-mail, scan to pdf	Four buttons: Start, copy, scan to e-mail, scan to pdf	Four buttons: Start, copy, scan to e-mail, scan to pdf	Four buttons: Start, copy, scan to e-mail, scan to pdf	One button: Start, customise with Epson Event Manager	One button: Start, customise with Epson Event Manager
Photo dust removal S/W / H/W	S/W: Yes H/W: No	S/W: Yes H/W: No	S/W: Yes H/W: No	S/W: Yes H/W: Digital ICE™	S/W: Yes H/W: Digital ICE™	S/W: Yes H/W: Digital ICE™ & FMA
Film dust removal S/W / H/W	S/W: N/A H/W: N/A	S/W: Yes H/W: No	S/W: Yes H/W: N/A	S/W: Yes H/W: Digital ICE™	S/W: Yes H/W: Digital ICE™	S/W: Yes H/W: Digital ICE™
Colour – restoration, descreening and backlight correction	Yes	Yes	Yes	Yes	Yes	Yes
SCANNING SPEED (seconds)						
Preview speed	13	13	13	13	10	10
A4 300dpi colour	14	14	14	14	14	14
35mm Negative 2400dpi	-	52	58	39	44	35 Faster than V700
35mm Positive 2400dpi	-	42	51	33	47	37 Photo due to 81 High-Pass optics
35mm Negative 4800dpi 35mm Positive 4800dpi	-	110 85	121 105	100 81	91 79	81 High-Pass optics
Somm Fositive 46000pi	-		105	01	19	
Bundled software	ArcSoft MediaImpression 2, ABBYY FineReader® Sprint Plus 9(Win®) / 8(Mac®)	ArcSoft Scan-n-Stitch <sup>™</sup> Deluxe, Arcsoft Medialmpression 2, ABBYY FineReader <sup>®</sup> Sprint Plus 9(Win <sup>®</sup> ) / 8(Mac <sup>®</sup> )	ArcSoft Scan-n-Stitch <sup>™</sup> , Adobe® Photoshop® Elements, ABBYY FineReader® Sprint Plus 6(Win®) / 5(Mac®)	ArcSoft Scan-n-Stitch <sup>™</sup> , Adobe® Photoshop® Elements, ABBYY FineReader® Sprint Plus 6(Win®) / 5(Mac®)	ArcSoft Scan-n-Stitch <sup>™</sup> , Silverfast SE, Adobe <sup>®</sup> Photoshop <sup>®</sup> Elements, ABBYY FineReader <sup>®</sup> Sprint Plus 6(Win <sup>®</sup> ) / 5(Mac <sup>®</sup> )	ArcSoft Scan-n-Stitch <sup>™</sup> , Silverfast Ai 6.6, MonacoEZColor, Adobe® Photoshop® Elements, ABBYY FineReader® Sprint Plus 6(Win®) / 5(Mac®)
Operating systems support	Windows®, Mac OS® X, Linux	Windows®, Mac OS® X, Linux	Windows <sup>®</sup> , Mac OS <sup>®</sup> X, Linux	Windows®, Mac OS® X, Linux	Windows®, Mac OS® X, Linux	Windows®, Mac OS® X, Linux
Power source	Wall mount	Wall mount	AC adapter	AC adapter	AC adapter	AC adapter
Power switch	Yes	Yes	Yes	Yes	Yes	Yes
Power consumption (Max)	12W	12W	16W	16.5W	32W	32W
Size and weight	280x430x40.8mm 2.20kg	430x280x66.5mm 2.83kg	272x475x113mm 4.0kg	280x485x118mm 4.0kg	503x308x152.5mm 6.6kg	503x308x152.5mm 6.6kg

<sup>1</sup> Charge-Coupled Device <sup>2</sup> Cold Cathode Fluorescent Lamp

 $\oplus$ 

 $\oplus$ 

 $\oplus$ 

 $\oplus$