C32G1

31.5 (80) LCD MONITOR





Flicker Free

AOC Flicker-Free Technology utilises a DC (Direct Current) backlight panel, reducing flickering light levels. With eye strain and fatigue absolutely minimized, feel free to enjoy those long, intense

gaming sessions in comfort!



FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain

slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.



144Hz Refresh Rate

Equip yourself with twice the frame rate of other monitors and say goodbye to image stuttering and blurry motion. With a 144Hz refresh rate every frame is rendered sharply and in smooth succession, so you can line up your shots accurately and appreciate high speed races in all their glory.

G1 Video marketing

Marketing video for G1 series



Minimal bezel distraction for the ultimate battle station

Expand your view with multiple monitor set-up. The narrow border and frameless design offer the minimal bezel distraction for the ultimate battle station.

1800R curvature

Curved design wraps around you putting you at the center of the action and provides an immersive gaming experience.

Screen Details

| Color | Black | |
|--------------------------|---|--|
| Resolution | 1920x1080 PX | |
| Refresh rate | 144Hz | |
| Response time | 1 | |
| Panel | VA | |
| Backlight | WLED | |
| sRGB Coverage (%) | 122 | |
| flickerfree | 1 | |
| Aspect ratio | 16:9 | |
| Brightness (typical) | 250 | |
| Contrast (dynamic) | 80M:1 | |
| Contrast (static) | 3000:1 | |
| Pixel Pitch (H) (V) | 0.3637 | |
| Diagonal (inch) | 31.5 | |
| Active Screen Area (HxW) | 698.4 x 392.85 mm | |
| Viewing angle (CR10) | 178/178 º | |
| Curvature Radius | 1800 mm | |
| Display Colours | 16.7 Million | |
| Weight without stand | 5.67 | |
| Adobe RGB Coverage (%) | 90 | |
| OSD languages | EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP | |
| Low blue light | v | |
| Connections | | |
| Signal Input | VGA, DisplayPort 1.2 x 1, HDMI 1.4 x 2 | |
| Audio output | Headphone out (3,5mm) | |
| | | |

What's in the box

HDMI cable (1,8 m), Displayport Cable (1,8 m), Power Cable C13 (1,8 m), $\ensuremath{\mathsf{m}}\xspace,$

Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

| _ | | | | |
|---|----|-----|---|----|
| | ra | on | m | CC |
| | IU | UII | | 60 |
| | | | | |

| Tilt | -5 ~ +21.5 ° |
|--------------------------------|---|
| Removable Stand | 1 |
| Vesa Wallmount | 100x100 |
| Power details | |
| Powersupply | External |
| Powersource | 100 - 240V 50/60Hz |
| Power Consumption | On 50 watt, Off 0.5 watt Standby 0.5 watt, |
| Dimensions | |
| Product Dimensions (incl base) | 530.3x713.1x244.9 mm |
| Product Dimensions (excl base) | 425.4x713.1x81.8 mm |
| CartonDimensions | 807x242x551 mm |
| Net Weight (excl package) | 6.98 |
| Gross Weight (incl package) | 9.1 |
| Warranty | |
| WarrantyPeriod | 3 Years |
| EAN | 4038986116510 |
| MTBF | 50.000 hours |
| | |

Regulations

