HP 20kd 49.53 cm (19.5") Monitor



Desirable quality. Smart savings.

With a sleek design and 1440x900 resolution¹, this affordable monitor delivers high-quality visuals at an irresistible price. Now you can enjoy a big screen view of your documents, photos, and movies without breaking the bank.



Feature-rich. Value-packed.

With an IPS panel, VGA and DVI inputs, WXGA+ (1440x900) resolution, and a 6000000:1 dynamic contrast ratio, enjoy crisp, clear quality at impressive viewing angles.

Liberate your desk space

Help keep your work space organized and clutter-free with a compact, eye-catching design and internal power supply that eliminates the need for a bulky power brick.

¹ WXGA+ content required to view WXGA+ images
³ EPEAT® Silver registered models of this product are available where HP registers consumer desktop computers.

HP 20kd 49.53 cm (19.5") Monitor

Featuring

Adjust your view

Adjust the screen to your personal preference with a 5° forward or 15° backward tilt.

Compact, sleek design

Get everything you need in one elegant package. Just one connection to the wall eliminates cable clutter. Slim design gives you more room for an enhanced computing experience.

HP Care Packs

Extend protection beyond the standard limited warranty with 7 days per week support and expedited repairs. Rest easy with the confidence of reliable service and the ability to count on your technology.⁵

Rest easy and work confidently with an HP standard 1 year limited warranty (vary by country). Certain restrictions and exclusions apply.⁶

⁴ Easy tilt 5° forward or 15° backward

HP 20kd 49.53 cm (19.5") Monitor







Display size	49.53 cm (19.5")
Display colors	Up to 16.7 million colors supported (through FRC technology)
Aspect ratio	16:9
Display type	LED backlight
Pixel pitch	0.29 mm
Response time	8 ms gray to gray
Brightness	250 cd/m²
Contrast ratio	1000:1 static; 6000000:1 dynamic
Display scan frequency (horizontal)	Up to 70 kHz
Display scan frequency (vertical)	Up to 75 Hz
Display features	Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable
Physical security features	Security lock-ready (lock is sold separately)
Environmental specifications	Mercury-free LED backlighting; Arsenic-Free Display Glass; Low Halogen
Display User Control Options	Brightness; Contrast; Color Control; Image Control; Power; Menu; Management; Information; Exit
Product dimensions	45.46 x 19.43 x 37.64 cm (with stand); 45.46 x 4.75 x 30.12 cm (without stand)
Weight	2.87 kg (with stand); 2.51 kg (without stand) 6.31 lb (with stand); 5.52 lb (without stand)
Operating temperature range	5 to 35 C
Operating humidity range	20 to 70 %
Certifications and compliances	CB; CE; FCC marking; ErP; CSA; C-UL; C-ETL Mark; UL; CSA-NTRL; ETL-NRTL Mark; ICES; Argentina S-Mark; Japan VCCI; CCC; China CEL; Taiwan BSMI; Bauart; ISO9241-307; GOST 25861; HRN N N0.201; GOST R 50377-1992; GOST 25861; EEI certificate; IS 1121; SASO; SABS IEC 60950-1; NOM-019-SCFI-1998; TCO Certified; SmartWay Transport Partnership (NA only);
Warranty	2-year limited warranty
What's in the box	A/C power cable (1.5 m), VGA cable (1.5 m), CD (include U.G., warranty, drives), Setup Poster
VESA mount	Yes
Product number	T3U83AA
Ordering info	889894803504

