

BRAVO Line IP Camera Series

TOP-107HMP

- H.264 Megapixel IP Dome Camera



FEATURES:

- H.264 / MPEG-4 / MJPEG Multi-Resolution Streaming simultaneous
- Megapixel Resolution at 1280 x 1024
- With 4.3 mm Fixed Lens
- Power over Ethernet (IEEE 802.3af) supported
- Supports 3GPP Mobile Surveillance and Internet Explorer Viewing
- Supports two way audio, Alarm Input / Output
- Free 64CH Management Software
- 10 Zones Hardware Motion Detection

SPECIFICATIONS

Pick-Up Device	1/4" Progressive Scan CMOS Sensor
Picture Elements	1280 x 1024 pixels
Minimum Illumination	1.0 Lux
Lens Type	4.3 mm Fixed Lens
CDS Sensor	Yes
Motion detection	10 zones
Video Compression	11 profiles simultaneously - H.264: SXGA, VGA, QVGA, QQVGA - MPEG4: VGA, QVGA, QQVGA - JPEG: SXGA, VGA, QVGA, QQVGA
Resolution	1280*1024 / 640*480 / 320*240 / 160*120
Image Frame rate	MegaPixel Mode : 15 FPS for 11 profiles VGA Mode : 30 fps for 9 profiles
Picture Adjustment	White Balance ; Color ; Brightness ; Contrast ; Sharpness ; Night Mode ; De-Noise;
Audio Support	AMR (3GPP) / G.726 (32 Kbps) / G.711 (64 Kbps)
Audio Input / Output	Line In / Line Out
Connectors	DI * 1 / DO * 1 / RS-485 * 1
Network	Ethernet (10/100 Base-T), RJ-45 Connector
Protocol	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, PPPoE, 3GPP, ICMP, Samba
UPnP	UPnP Discover, and UPnP Auto port forwarding
OS	Windows® 2000, XP, Vista
Browser	IE 6.0 or later / Firefox
Mobile Phone	3GPP mobile surveillance. Audio+video
Clients (simultaneously)	20
Power	DC 12V / PoE (IEEE 802.3af)
Power Consumption	5W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20% ~ 80% (non-condensing)
SDK	API / CGI documentation

