

# UTC-VLP4526T

## Colour Mono Camera c/w Lens & IR LED



■ CCD	1/3"
■ Resolution Colour	600 TVL
■ Sensitivity Mono	0.0 Lux IR LED ON
■ Infra Red IR LEDs	50 (Hybrid)
■ IR Range	100m
■ Lens Size	6-50mm Varifocal
■ Voltage	12V DC
■ Power Consumption	110mA (Max)
■ Dimensions	320x265x240mm
■ Weight	2600g

### Other Features

- Day Night
- Auto White Balance
- Auto Gain Control
- IP65
- Internal / External
- Weatherproof

Image Pick-up Device	1/3" Sony Color Super HAD II CCD
Total Pixels	N: 811(H) x 508 (V) / P: 795 (H) x 596 (V)
Effective Pixels	N:768(H) x 494 (V) / P: 752 (H) x 582 (V)
Scanning System	[ 2:1 interlaced (NTSC) 525 lines / (PAL) 625 lines ]
Scanning Frequency	[ NTSC : 15,734KHz (H) / 59.94Hz ] / [ PAL : 15,625KHz (H) / 50Hz ]
Horizontal Resolution	COLOR : 600 TV Lines (Typ)
Electronic Shutter Speed	N : 1/60 sec ~ 1/110,000 sec,P :1/50 sec ~ 1/120,000 sec
Minimum Illumination	0.01Lux/0.000 Lux ( IR ON )
OSD Menu	Built-in
Motion Detection	ON(4 Area) / OFF
Lens Shading	ON / OFF
2D-DNR	ON / OFF
Privacy	ON / OFF (8 Zone)
Sharpness & Saturation	ON / OFF (Level Adjustable)
Parking Line	ON / OFF
Operating Humidity	30 ~ 80% RH
Dimensions	320mmX265mmX240mm

S/N Ratio (Y signal)	52dB (AGC Off, Weight On)
Backlight Compensation	Selectable/BLC/HLC/OFF
Synchronous System	Internal
Day & Night Selection	COLOR / B/W / AUTO/ EXT
Video Output	VBS : 1.0Vp-p, 75 Ohm composite
Gain Control	LOW / MIDDLE / HIGH / OFF Selectable
White Balance	ATW1/ATW2/MANUA/ATW1 (2300°K ~ 9500°K); ATW2(2000°K ~ 11000°K)
IR SMART	OFF
Mirror (H-REV)	OFF
Blemish Compensation	64 points
Lens mount	6-50mm Auto-iris zoom lens with IR-CUT
LED Quantity	50pcs
IR-CUT filter	Available
IR Range	100m
Power Consumption	DC 12V ± 10%,110mA(max:1.2A)
Operation Temperature	-10°C ~ +50°C
Weight	Appx. 2600g

