

UTC-DSIR-W

Vandal Resistant IR Dome Camera



■ CCD	1/3"
■ Resolution Colour	420 TVL
■ Sensitivity Mono	0.0 Lux IR LED ON
■ Infra Red IR LEDs	23
■ IR Range	20m
■ Lens Size	3.6mm
■ Voltage	12V DC
■ Power Comsumption	300mA (Max)
■ Dimensions	94øx80mm
■ Weight	370g

Other Features

- Auto White Balance
- Auto Gain Control
- Back Light Compensation
- Tri-Axis Gimbal

Type	Color/Monochrome
Signal System	NTSC/PAL
Pick Up Device	Color 1/3" CCD
Picture Elements	NTSC:510Hx492V; PAL:500Hx582V
Resolution	420TVL
Min Illumination	0 Lux(with IR LED ON)
Vertical Frequency	NTSC:60Hz; PAL:50Hz
Horizontal Frequency	NTSC:15.734KHz; PAL:15.625KHz
Clock Frequency	NTSC:28.636MHz; PAL:28.375MHz
Scanning System	2:1 Interlace
S/N Ratio	≥48dB
Electronic Shutter	NTSC:1/60-1/100,000s; PAL:1/50-1/100,000s

Lens	3.6mm Lens
White Balance	AUTO Tracking
Back Light	ON
Auto Gain Control	ON
GAMMA	0.45
Video Out-put	1V p-p,75 Ohm
Power Supply	DC12V ±10%
Current Consumption	300mA(Max)
Dimension	94øx80mm
Weight	370g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+50°C

