

UTC-DSIRHURV

Vandal Resistant IR Dome Camera



■ CCD	1/3"
■ Resolution Colour	700 TVL
■ Sensitivity Mono	0.0 Lux IR LED ON
■ Infra Red IR LEDs	36
■ IR Range	30m
■ Lens Size	4-9mm Varifocal
■ Voltage	12V DC
■ Power Comsumption	400mA (Max)
■ Dimensions	120øx100mm
■ Weight	580g

Other Features

- Auto White Balance
- Auto Gain Control
- Back Light Compensation
- Tri-Axis Gimbal

Type	Color/Monochrome
Signal System	NTSC/PAL
Pick Up Device	Color 1/3" CCD
Picture Elements	NTSC:811Hx508V; PAL:795Hx596V
Resolution	700TVL
Min Illumination	0 Lux(with IR LED ON)
Vertical Frequency	NTSC:60Hz; PAL:50Hz
Horizontal Frequency	NTSC:15.734KHz; PAL:15.625KHz
Clock Frequency	NTSC:28.636MHz; PAL:28.375MHz
Scanning System	2:1 Interlace
S/N Ratio	+63dB
Electronic Shutter	NTSC:1/60-1/100,000s; PAL:1/50-1/100,000s

Lens	4-9mm Varifocal Fixed Iris Lens
White Balance	AUTO Tracking
Back Light	ON
Auto Gain Control	ON
GAMMA	0.45
Video Out-put	1V p-p,75 Ohm
Power Supply	DC12V ±10%
Current Consumption	400mA(Max)
Dimension	120øx100mm
Weight	580g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+50°C

